

Delcan Products Ltd.

09/2010

1409 5th Avenue P.O. Box 391

Fort Macleod, AB T0L 0Z0

Phone (403) 553-3632

Fax (403) 553-3660

Website www.delcanproducts.com

E-mail info@delcanproducts.com

Product Guide Specification

Specifier Notes: This product guide specification is written according to the Construction Specifications Institute (CSI) 3-Part Format, including Master Format, Section Format, and Page Format, as described in The Project Resource Manual—CSI Manual of Practice.

The section must be carefully reviewed and edited by the Architect to meet the requirements of the project and local building code. Coordinate this section with other specification sections and the Drawings. Delete all "Specifier Notes" when editing this section.

Section numbers are from Master Format 1995 Edition, with numbers from Master Format 2004 Edition in parentheses. Delete version not required.

SECTION 06600 (06 64 00)

PVC WALL PANELING

Specifier Notes: This section covers Delcan Products Ltd. DelPro 1238™ exterior-grade PVC wall & ceiling panels. Consult Delcan Products Ltd. for assistance in editing this section for the specific application

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Exterior-grade PVC wall panels.

1.2 RELATED SECTIONS

Specifier Notes: Edit the following list of related sections as required for the project. List other sections with work directly related to this section.

- A. Section 07920 (07 92 00) – Joint Sealants.

1.3 REFERENCES

Specifier Notes: Edit the following list of related sections as required for the project. List other sections with work directly related to this section.

- A. ASTM E 84 – Standard Test Method for Surface Burning Characteristics of Building Materials.

1.4 SUBMITTALS

- A. Comply with Section 01330 (01 33 00) – Submittal Procedures.
- B. Product Data: Submit manufacturer's product data, including the following:
 - 1. Panel and trim details.
 - 2. Installation instructions.
- C. Samples:
 - 1. Submit manufacturer's samples of Interlocking PVC Wall & Ceiling Panels, including tongue-and-groove edges and nailing fins.
 - 2. Submit manufacturer's samples of each type of trim to be installed.
- D. Manufacturer's Certification: Submit manufacturer's certification that materials comply with specified requirements and are suitable for intended application.
- E. Maintenance Instructions: Submit manufacturer's maintenance and cleaning instructions.
- F. Warranty: Submit manufacturer's standard warranty.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Delivery: Deliver materials to site in manufacturer's original, unopened containers and packaging, with labels clearly identifying product name and manufacturer.
- B. Storage:
 - 1. Store materials in clean, dry area indoors in accordance with manufacturer's instructions.
 - 2. Store DelPro 1238™ Interlocking PVC Wall & Ceiling Panels flat.
- C. Handling: Protect materials during handling and installation to prevent damage.

1.6 ENVIRONMENTAL REQUIREMENTS

- A. Installing Interlocking PVC Wall & Ceiling Panels:
 - 1. Cold Temperatures: When installing DelPro 1238™ Interlocking PVC Wall & Ceiling Panels in temperatures below 4°C, leave space between panels to allow for expansion in accordance with manufacturer's instructions.
 - 2. Warm Temperatures: When installing DelPro 1238™ Interlocking PVC Wall & Ceiling Panels in temperatures above 30°C, warm panels to a minimum of 20°C in accordance with manufacturer's instructions.
- B. Cutting Interlocking PVC Wall & Ceiling Panels:
 - 1. Cold Temperatures: Before field-cutting DelPro 1238™ Interlocking PVC Wall & Ceiling Panels in temperatures below 4°C, warm panels to a minimum of 10°C overnight.

1.7 WARRANTY

- A. Warranty Period for Interlocking PVC Wall & Ceiling Panels: 15 years.

PART 2 PRODUCTS

2.1 MANUFACTURER

Westech Building Products
5201 64th Ave SE
Calgary, AB T2C 4Z9
Phone (403) 279-4497
Fax (403) 279-4790

2.2 PVC WALL & CEILING PANELS

- A. DelPro 1238™ Interlocking PVC Wall & Ceiling Panels
1. Description: Tongue-and-groove, a rib-reinforced interlocking PVC wall & ceiling panel with nailing fins.
 2. Material: 100 percent virgin, exterior-grade PVC.
 3. Outside Surface: Flat.
 4. Width: 12 inches.
 5. Thickness: 3/8 inch.
 6. Weight: 0.85 pound per square foot.
 7. Surface Burning Characteristics, ASTM E 84:
 - a. Flame Spread Index: 10.
 - b. Smoke Developed Index: 450.
 8. Color: White, glossy finish.
- B. Trim:
1. Material: 100 percent virgin, exterior-grade PVC.
 2. Weight: 0.06 pound per linear foot.
 3. Color: Same as DelPro 1238™ Interlocking PVC Wall & Ceiling Panels.

2.3 ACCESSORIES

- A. Construction Adhesive: PL200 or Liquid Nails, as recommended by wall panel manufacturer.
- B. Fasteners:
1. Fastening into Wood: Stainless steel, 1-inch, No. 10 truss-head sheet metal screws.
 2. Fastening into Masonry: Stainless steel, Buildex Tapcon 3/16-inch by 1-1/4-inch screws, with 1/4-inch stainless steel washers.
 3. Fastening into Metal: Stainless steel, 3/4-inch, No. 10 truss-head sheet metal or flat-head Tek screws.
 4. Staples: Do not use.

Specifier Notes: Specify the section number for joint sealants.

- C. Joint Sealants: As specified in Section 07920 (07 92 00).

PART 3 EXECUTION

3.1 EXAMINATION

- A. Examine areas to receive DelPro 1238™ Interlocking PVC Wall & Ceiling Panels.
- B. Notify Architect of conditions that would adversely affect installation or subsequent use.
- C. Do not begin preparation or installation until unacceptable conditions are corrected.

3.2 PREPARATION

- A. Prepare DelPro 1238™ Interlocking PVC Wall & Ceiling Panels for installation in accordance with manufacturer's instructions.
- B. Ensure DelPro 1238™ Interlocking PVC Wall & Ceiling Panels are dry and clean.

3.3 INSTALLATION

- A. Install DelPro 1238™ Interlocking PVC Wall & Ceiling Panels in accordance with manufacturer's instructions at locations indicated on the Drawings.
- B. Install DelPro 1238™ Interlocking PVC Wall & Ceiling Panels plumb, level, square, flat, and in proper alignment.
- C. Install trim in accordance with manufacturer's instructions.
- D. Anchor DelPro 1238™ Interlocking PVC Wall & Ceiling Panels with construction adhesive and fasteners in accordance with manufacturer's instructions.
- E. Fasteners:
 - 1. Install fasteners 16 inches to 24 inches on center into nailing fins.
 - 2. Keep top of screw head 1/16 inch above top of nailing fins, allowing panels to move slightly.
 - 3. Do not recess screw heads into nailing fins.
 - 4. Ensure nailing fins lay flat against surface, not deformed around screw heads.
 - 5. Ensure fasteners are not exposed.
- F. Cutting Interlocking PVC Wall & Ceiling Panels:
 - 1. Field-cut panels as necessary in accordance with manufacturer's instructions.
 - 2. Ensure cuts are straight, square, and do not damage panels.

Specifier Notes: Specify the section number for joint sealants.

- G. Apply joint sealants as specified in Section 07920 (07 92 00).

3.4 ADJUSTING

- A. Repair minor damages to finish in accordance with manufacturer's instructions and as approved by Architect.
- B. Remove and replace damaged DelPro 1238™ Interlocking PVC Wall & Ceiling Panels in accordance with manufacturer's instructions.

3.5 CLEANING

- A. Clean DelPro 1238™ Interlocking PVC Wall & Ceiling Panels promptly after installation in accordance with manufacturer's instructions.
- B. Do not use harsh cleaning materials or methods that could damage finish.

3.6 PROTECTION

- A. Protect installed DelPro 1238™ Interlocking PVC Wall & Ceiling Panels from damage during construction.

END OF SECTION